











Product specification	PRO 4K65	PRO 4K80
Build Volume X, Y, Z	176.5 x 99 x 200mm. 6.94 x 3.9 x 7.87 inches	217 x 122 x 200mm. 8.54 x 4.8 x 7.87 inches
Pixel Resolution	65µm	80µm
Technology	DLP	DLP
LED Wavelength	385nm (high power UV LED) or 405nm	385nm (high power UV LED) or 405nm
		•
Material Compatibility	Asiga materials. 100% Open Material System - use any suitable 3rd party material	
Software	Asiga Composer software. Lifetime updates included	
File inputs	STL, SLC, STM (Asiga Stomp file format)	
Network Compatibility	Wifi, WirelessDirect, Ethernet	
Power requirements	100-240VAC, 50/60Hz, 500 Watts (100V - 5Amp Max. 240V - 2.1Amp)	
System sizing	465 x 420 x 1370mm / 75Kg. 18.3 x 16.5 x 53.9 inches / 165Lbs	
Packed sizing	975 x 735 x 1590mm / 100Kg. 38.3 x 28.9 x 62.6 inches / 220Lbs	
Warranty	12 months manufacturers warranty	
Technical support	Unlimited lifetime technical support included	
Bundle includes	3D printer, Composer software, 1Kg Asiga material, 1L build tray, Asiga Flash post-curing chamber, calibration toolkit	

